The California Central Valley Groundwater-Surface Water Simulation Model

Summary

CWEMF C2VSim Workshop January 23, 2013

Charles Brush

Modeling Support Branch, Bay-Delta Office California Department of Water Resources, Sacramento, CA

Acknowledgements

Tariq Kadir, Can Dogrul, Francis Chung, Sushil Arora, Michael Moncrief¹, Guobiao Huang, Jane Shafer-Kramer, Messele Ejeta, Liheng Zhong, Linda Bond, Chris Bonds, Dong Chen, Jeff Galef, Todd Hillaire, Abdul Khan, Seth Lawrence, Dan McManus, Paul Mendoza, Chris Montoya, Bob Niblack, Scott Olling, Eric Senter, Steven Springhorn, Jean Woods and Brett Wyckoff, DWR

Steve Shultz, Dan Wendell² and Rob Leaf, CH₂M Hill

Matt Tonkin and Gil Barth, SS Papadopulos & Associates

Zhaojun Bai, Matthew Dixon³ and Hieu Nguyen⁴, CSE, UC Davis

Andy Draper and Jafar Faghih, MWH Global


Ali Taghavi, Reza Namvar and Mesut Cayar, RMC-WRIME

Walter Bourez and Lee Bergfeld, MBK Engineers

Charles Burt and staff, ITRC; Claudia Faunt, USGS

currently with: (1) MBK Engineers, (2) Groundwater Dynamics, (3) U. of San Francisco, (4) U. of Edinburgh

Integrated Water Flow Model (IWFM)



IWFM Documentation

- Theoretical documentation, user's manual, reports, technical memorandums, previous presentations and posters, user's group presentations, and published articles in peer reviewed journals are available at the IWFM web site (google "IWFM")
- Technical support by DWR staff

Integrated Water Flow Model
IWFM v3.02

Theoretical Documentation

Integrated Hydrological Models Development Unit Modeling Support Branch Bay-Delta Office October 2011



Integrated Water Flow Model IWFM v3.02

User's Manual

Integrated Hydrological Models Development Unit Modeling Support Branch Bay-Delta Office October 2011



Z-Budget: Sub-Domain Water Budgeting Post-Processor for IWFM

Theoretical Documentation and User's Manual

Hydrology Development Unit Modeling Support Branch Bay-Delta Office February, 2010



IWFM Applications


- California Central Valley Groundwater-Surface Water Model (C2VSim)

- Butte County Groundwater Model (Heywood, CDM)

- Walla Walla River Basin Model (Petrides, OSU)

Yolo County Integrated Model







Derived from the CVGSM model

- WY 1922-1980 Boyle & JM Montgomery (1990)
- WY 1981-1998 CH₂M Hill for CVPIA PEIS

Steady modification

- DWR IWFM/C2VSim development began in 2000
- IWFM process and solver improvements
- C2VSim data sets reviewed and refined
- C2VSim input data extended through WY 2009

Calibration

- PEST parameter estimation program
- Three phases: Regional, Local, Nodal
- Calibration Period: WY 1973-2003 in phases 1 & 2, 1922-2004 in phase 3

C2VSim Versions

C2VSim CG 3.02 (R367): Release Version

- Current version, updated November 2012
- Water Years 1922-2009, monthly time step
- IWFM version 3.02

C2VSim FG 3.02 (R356): Draft Version

- Based on C2VSim 3.02 CG of Jan 2012
- Refine rivers, inflows, land use
- Update to current CG version
- Expected release in Summer 2013

Planned Improvements

- C2VSim 3.02 CG/FG: Extend to WY 2011 or 2012
- C2VSim 4.0 FG: Element-level land use, crop and diversion data



"C2VSim CG-3.02"

Finite Element Grid

- 3 Layers or 9 Layers
- -1393 Nodes & 1392 Elements

Surface Water System

- 75 River Reaches, 2 Lakes
- 243 Surface Water Diversions
- -38 Inflows, 11 Bypasses
- 210 Small-Stream Watersheds


Land Use Process

- 21 Subregions (DSAs)
- 4 Land Use Types

Simulation periods

- -10/1921-9/2009 (88 yrs)
- runs in 3-6 min

IWFM version 3.02



C2VSim Fine Grid

"C2VSim FG-3.02"


	Coarse Grid	Fine Grid
Nodal Spacing		
Minimum	0.6 mi	0.4 mi on rivers
Maximum	9.4 mi	1.5 mi on edge
Average	14.4 mi ²	0.6 mi ²
Model Grid		
Nodes	1,393	30,179
Elements	1,392	32,537
River nodes	449	4,529
Run Time		
88 years	3-6 min	Appx 6 hrs

Suggested uses:

- CG region-scale analyses
- FG local-scale analyses


Beta release after staff review


- Expected release Spring 2013
- Integrated with C2VSim ArcGIS GUI





Hydraulic Conductivity


Layer 1 Layer 2

















C2VSim Publications




Excel Add-In




HEC-DSS



TecPlot-Ready Output



C2VSim ArcGIS Tool



C2VSim Uses

- CalSim 3 groundwater component
- Integrated Regional Water Management Plans
- Stream-groundwater flows
- Climate change assessments
- Groundwater storage investigations
- Planning studies
- Ecosystem enhancement scenarios
- Infrastructure improvements
- Impacts of operations on Delta flows



- Groundwater Substitution Water Transfer:
 Sacramento Valley Water Management Program
- Potential Impacts of Climate Change I: Aquifer Response to Extended Drought
- Potential Impacts of Climate Change II: Aquifer Response to Extended Drought with Economic Adaptation
- GRACE Collaboration: Downscaling Remote Sensing Observations with C2VSim




Sacramento Valley Water Management Program

- Sacramento Valley Water Mgmt. Agreement
 - SWRCB D-1641, A15
 - Sacramento Valley water users
 - California DWR
 - USBR
 - Export water users
- Conjunctive water management projects
 - Groundwater substitution for surface water
 - Approximately 30 participants
 - Operate in non-wet years (Sacramento River Index)
 - 173 TAF/year, June 1 October 31

C2VSIM Simulation of the SVWMP

- Identify individual wells and pumping rates
- Prepare IWFM input files
 - October 1972 September 2003 Hydrology
 - Pumps run Jun-Oct in non-wet years
- C2VSIM runs
 - 1. Turn on groundwater adjustment
 - 2. Turn on surface water adjustment
 - 3. Turn on SVWMP wells & reduce diversions in non-wet years (Sacramento River Index)

Sacramento Valley Water Management Program



Use groundwater in lieu of surface water

SVWMP Wells

- 29 Districts
- 293 wells
- 187,633 AF/year

Operate non-wet years

- 1973 1 yr

- 1976-81 6 yrs


– 19851 yr

- 1987-94 8 yrs

- 2000-03 4 yrs


Sacramento Valley Water Management Program

C2VSIM Diversions





- Adjusted:
 - 19 diversions above Freeport
- Unadjusted:
 - 11 imports
 - 2 exports

Flow Difference (SVWMP – Base Case)





Percent Flow Difference (SVWMP – Base Case)











Preliminary Findings

- C2VSIM simulation of SVWMP operations
 - SVWMP simulation is easy to implement in C2VSIM
 - Summer flow increase at Freeport averages 128 MAF (68%)
 - Multi-year impacts are very important
 - Annual flow loss at Freeport as groundwater recovers
 - Lots of information areal recharge, storage, GW-SW
- Issues regarding C2VSIM and SVWMP
 - Scale: C2VSIM is a 'regional' model
 - Water budget: Subregional 'virtual farms'
 - All currently being addressed in continued development of C2VSIM and IWFM




- I: Aquifer Response to Extended
 Drought
- II: Linking Economic and Hydrologic Models to Study Impacts with Economic Adaptation

Norman L. Miller and Larry L. Dale, Lawrence Berkeley national Laboratory and UC Berkeley

Sebastian D. Vicuna, UC Berkeley and Centro Interdisciplinario de Cambio Global, Pontificia Universidad Catolica de Chile

Charles F. Brush, Emin C. Dogrul, Tariq N. Kadir and Francis I. Chung California Department of Water Resources

Climate Variability



Water Year (October 1 - September 30)

Sources: DRI 2008, 2009; CalEPA 2009; CNRA 2009; Mosher et al. 2009


Methods

- Use historical 1972-2003 data to construct 10-year monthly valley-rim inflows for (1) base case, (2) slight, (3) moderate and (4) severe droughts
- Develop diversion scenarios using CALSIM-II
- Determine economic parameters using CVPM
- Integrated hydrologic simulations with C2VSIM
 - 10-year spin-up at 'average' conditions
 - 10-, 20-, 30- or 60-year drought
 - 30-year recovery period
 - Calculate groundwater pumping to meet demands
- Incorporate economic factors using Logit functions
 - Fixed agricultural water demand
 - Variable agricultural water demand

Central Valley Water Table 'Relative' Response

Joint LBNL-DWR Drought Simulation

30-percent reduction in surface water inflows




"Drought Resilience Of The California Central Valley Surface-Groundwater-Conveyance System" by N. L. Miller et al. Submitted to <u>J. Am. Water Res. Assoc</u>. April 2008.

Central Valley Water Table 'Relative' Response


Joint LBNL-DWR Drought Simulation

70-percent reduction in surface water inflows



"Drought Resilience Of The California Central Valley Surface-Groundwater-Conveyance System" by N. L. Miller et al. Submitted to <u>J. Am. Water Res. Assoc</u>. April 2008.

Depth to Groundwater – Constant Crops






- Crop mix is a function of water cost
 - Surface water availability
 - Depth to groundwater
 - Crop water demand
 - Crop production costs and returns
- Incorporate Logit equation in IWFM application

$$\alpha_{ir} = \frac{e^{x_r \beta_{ir}}}{1 + \sum_{j} e^{x_r \beta_{jr}}}$$


 Determine Logit equation parameters from a series of simulations conducted with the Central Valley Production Model

Water Use

Severe drought for 60 years




Crop Changes Severe drought for 60 years




Depth to Groundwater


Severe drought for 60 years



Water Table at End of Drought



Depth to Groundwater – Compare



Findings

- Regional impacts of extreme drought
 - Moderate in north (Sacramento River Basin)
 - Locally severe in middle (San Joaquin River Basin)
 - Severe in south (Tulare Basin)
- Economic behavior may significantly reduce drought impacts below levels projected using a fixed level of future development
- The C2VSIM integrated model with CVPM emulation
 - performs as expected
 - can provide valuable insights into the impacts of climate change on Central Valley aquifers and on Central Valley agriculture

Publications

Miller, Dale, Brush, Vicuna, Kadir, Dogrul and Chung. 2009. Drought resilience of the California Central Valley surface-groundwater-conveyance system. JAWRA 45:857-866.



Dale, Dogrul, Brush, Kadir, Chung, Miller, and Vicuna. Simulating the Impact of Drought on Central Valley Hydrology, Groundwater, and Cropping. Submitted to British Journal of Environment and Climate Change Nov. 2012.

Future Work

- Develop more realistic drought scenarios
 - Downscale GCM precipitation and use VIC to simulate rim inflows
 - Monte Carlo simulations
 - Changes in amount and timing of crop water demands
 - Changes in amount and timing of reservoir releases
 - More elaborate economic model
- More complex variable-crop drought simulations
 - Economic parameters from SWAP
 - More detailed model subregions

Downscaling GRACE Satellite Data for Small-scale Groundwater Storage Estimates in California's Central Valley

NASA DEVELOP Team:

Amber Jean Kuss^{1, 2}

Michelle Newcomer^{1, 3}


Wei-Chen Hsu^{1,3}

Abdelwahab Bourai^{1,4}

Abhijitkrishna Puranam^{1, 5}

Felix Landerer⁶

Cindy Schmidt^{1,7}




¹NASA Ames DEVELOP, ²University of California, Santa Cruz, ³University of California, Berkeley, ⁴Carnegie Mellon University, ⁵Saint Francis High School, ⁶NASA Jet Propulsion Laboratory, ⁷Bay Area Environmental Research Institute




GRACE Satellites




GRACE Earth Gravity Anomaly



GRACE Earth Gravity Anomaly



GRACE Gravity Model




GRACE to Groundwater Storage

Change in Groundwater =

Total Change in Gravity


- Change in atmospheric moisture
- Change in snowpack
- Change in reservoir storage
- Change in soil moisture
- Change in petroleum reserves
- Change in tidal water

Compare GRACE and C2VSim




Groundwater Storage Estimates


C2VSim Change in Groundwater Storage October 2004 - September 2009




Downscaled GRACE Change in Groundwater Storage October 2004 - September 2009




Downscale to Subregion 19




Downscaled Estimates






GRACE Groundwater Storage Anomalies - March 2009




Subregional Change in Storage



Preliminary Findings

- GRACE provides reasonably accurate estimates of the change in groundwater storage in near-real time for large areas (Central Valley) and long time frames (1 year)
- GRACE loses accuracy as the time and/or area are reduced
- GRACE results can be downscaled using C2VSim

Change in Groundwater Storage



National Drought Mitigation Center. (n.d.) Groundwater and soil moisture conditions from GRACE data assimilation.

Tomorrow

- Running C2VSim
- Using the C2VSim ArcGIS GUI
- Groundwater Pumping Case Study
 - Add some pumps to the model
 - See the changes in heads and river flows
- Aquifer Storage and Recovery Case Study
 - Modify a diversion and add a pump
 - See the changes in heads and river flows

